



Cartridge Filter Specifications

204401.202

Dimensions:	Height:	39.00"
	Outside Diameter:	13.50"
	Inside Diameter:	10.75"
Top End Cap:	Material:	Electro Galvanized
	Style:	Oval, Open
Bottom End Cap:	Material:	Electro Galvanized
	Style:	Oval, Closed
Gasket:	1/2" x 5/8" x 13.875" & .560" x 5/8" x 11.25" ID isoprene sponge applied on top cap	
Outer Retainer:	Helical Cording	
Inner Core:	Electro Galvanized expanded metal 3/8" x 5/8" 72% open area Spiral Heli-Coil with Metal Channel Lock	
Filter Media Area:	~400 ft ²	
Media Type:	Fire Retardant Nanofiber	
Permeability:	20 cfm/ft ² @ 0.5" w.g.	
Temperature Rating:	180° F.	
Minimum Efficiency:	MERV 15 @ 900cfm	

Minimum Efficiency			
Minimum Average Efficiency	(E1) 0.3 - 1.0 86%	(E2) 1.0 - 3.0 97%	(E3) 3.0 - 10.0 100%

Data per ASHRAE Test Standard 52.2 - Independently tested to ensure validity - Test reports provided upon request.

Contact Imperial Systems Parts & Service team
for all your dust collection filter, parts, and service needs.

800.918.3013 | www.ImperialSystemsInc.com