



Cartridge Filter Specifications

DeltaMAXX Prime **204401207**

Dimensions:	Height:	39.00"
	Outside Diameter:	13.50"
	Inside Diameter	10.75"
Top End Cap:	Material:	Electro galvanized with DeltaMAXX Prime Flange
	Style:	Oval, Open
Bottom End Cap:	Material:	Electro galvanized
	Style:	Oval, Closed
Gasket:	1/2" x 5/8" x 13.875 & 13.875" Single piece double gasket open cell sponge	
Outer Retainer:	3 woven bands	
Inner Core:	Electro galvanized expanded metal 3/8" x 5/8" 72% open area with ground wire	
Filter Media Area:	~245 ft ²	
Permeability:	20 cfm/ft ² @ 0.5" w.g.	
Media Type:	100% Spunbond polyester	
Temperature Rating:	265°F	

Minimum Efficiency

Minimum Average
Efficiency

(E1) 0.3 - 1.0
56%

(E2) 1.0 - 3.0
74%

(E3) 3.0 - 10.0
97%

Data per ASHRAE Test Standard 52.2 - Independently tested to ensure validity - Test reports provided upon request.

Contact Imperial Systems Parts & Service team
for all your dust collection filter, parts, and service needs.

800.918.3013 | www.ImperialSystemsInc.com